



## Specifications



# TRUTH B2030A/B2031A

High-Resolution, Active 2-Way Reference Studio Monitor

- **B2030A:**
  - Built-in 125-Watt power amp with enormous power reserve
  - Long-throw 6 ¾" woofer with special polypropylene diaphragm and deformation-resistant aluminum die-cast chassis
- **B2031A**
  - Built-in 265-Watt power amp with enormous power reserve
  - Long-throw 8 ¾" woofer with special polypropylene diaphragm and deformation-resistant aluminum die-cast chassis
- Ultra-linear frequency response from 50 Hz to 21 kHz with individual frequency diagrams
- Ultra-high resolution ferrofluid-cooled tweeter
- Controlled dispersion characteristics and extremely large "sweet spot" owing to the unique BEHRINGER wave guide technology
- Active crossover network with 4th order Linkwitz-Riley filters
- Adjustable to a wide range of acoustic conditions and subwoofer operation
- Separately controlled limiter for low and high frequency overload protection
- Automatic standby mode (defeatable)
- Magnetic shielding allows placement near computer monitors
- Delivered as "matched pairs" with individual frequency diagrams
- Servo-balanced inputs with XLR and ¼" TRS connectors
- High-quality components and exceptionally rugged construction ensure long life
- Conceived and designed by BEHRINGER Germany

## Legal Disclaimer

Technical specifications and appearance are subject to change without notice. The information contained herein is correct at the time of printing. All trademarks are the property of their respective owners. MUSIC Group accepts no liability for any loss which may be suffered by any person who relies either wholly or in part upon any description, photograph or statement contained herein. Colors and specifications may vary slightly from product. BEHRINGER products are sold through authorized dealers only. Distributors and dealers are not agents of MUSIC Group and have absolutely no authority to bind MUSIC Group by any express or implied undertaking or representation. This manual is copyrighted. No part of this manual may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording of any kind, for any purpose, without the express written permission of Red Chip Company Ltd.

ALL RIGHTS RESERVED.

© 2010 Red Chip Company Ltd.

Trident Chambers, Wickhams Cay, P.O. Box 146,  
Road Town, Tortola, British Virgin Islands

# Specifications

## Audio Inputs

### B2030A/B2031A

XLR connector	servo-balanced input
¼" TRS	servo-balanced input
Input impedance	10 kΩ
Max. input level	+22 dBu

## Components

### B2030A

Tweeter	¾" ferrofluid-cooled dome
Woofers	6 ¾" polypropylene diaphragm

### B2031A

Tweeter	1" ferrofluid-cooled dome
Woofers	8 ¾" polypropylene diaphragm

## Amplifier

### B2030A

RMS @ 0.1 % THD	70 W
Peak power	125 W

### B2031A

RMS @ 0.1 % THD	140 W
Peak power	265 W

## Crossover

### B2030A/B2031A

Type	active, 4th order Linkwitz-Riley
Crossover frequency	2 kHz

## System Specification

### B2030A

Frequency response	50 Hz to 21 kHz
Sound pressure level	max. 113 dB SPL @ 1 m (pair)

### B2031A

Frequency response	50 Hz to 21 kHz
Sound pressure level	max. 116 dB SPL @ 1 m (pair)

## Power Supply

### B2030A

#### Voltage/Fuses

100 - 120 V~, 50/60 Hz	T 2.0 A H 250 V
220 - 230 V~, 50/60 Hz	T 1.6 A H 250 V

#### Voltage/Supply current

100 - 120 V~, 50/60 Hz	max. 1.0 A
220 - 230 V~, 50/60 Hz	max. 0.5 A

#### Mains connection

Standard IEC connector

### B2031A

#### Voltage/Fuses

100 - 120 V~, 50/60 Hz	T 5.0 A H 250 V
220 - 230 V~, 50/60 Hz	T 2.5 A H 250 V

#### Voltage/Supply current

100 - 120 V~, 50/60 Hz	max. 2.0 A
220 - 230 V~, 50/60 Hz	max. 1.1 A

#### Mains connection

Standard IEC connector

## Dimensions/Weight

### B2030A

Dimensions (H x W x D)	12 ½ x 8 ⅝ x 8 ⅛" 317 x 214 x 211 mm
Weight	21 ⅔ lbs / 9.84 kg

### B2031A

Dimensions (H x W x D)	15 ¾ x 9 ⅜ x 11 ⅜" 400 x 250 x 290 mm
Weight	33 lbs / 15 kg

BEHRINGER is constantly striving to maintain the highest professional standards. As a result of these efforts, modifications may be made from time to time to existing products without prior notice. Specifications and appearance may differ from those listed or illustrated.



imagine music