

ULTRABASS

BX3000T



Technical Specifications


Version 1.1 October 2003

ENGLISH

ULTRABASS BX3000T

ULTRABASS

300-Watt bass amplifier with DYNAMIZER technology



- ▲ Extremely powerful 300-Watt RMS bass amp head
- ▲ Patented* DYNAMIZER technology for ultimate punch
- ▲ Switchable ULTRABASS sub-harmonics processor for unbelievable low-end power
- ▲ Revolutionary SHAPE filter for extreme sound range
- ▲ Extremely musical 5-band EQ with “Bright” and “Deep” functions for ultimate tone-shaping
- ▲ Integrated limiter and active, temperature-controlled cooling system for ultimate protection
- ▲ Vintage-style VU meter for precise signal level control
- ▲ Dual footswitch for ULTRABASS and SHAPE functions included
- ▲ Balanced XLR DI output, easily accessible on the front panel
- ▲ Effects loop with tuner function and line output for additional flexibility
- ▲ 3 speaker outputs on 1/4" jack and SPEAKON® connectors
- ▲ Ultra-rugged power supply with toroidal transformer for highest power reserves
- ▲ Extremely rugged construction ensures long life, even under the most demanding conditions
- ▲ Designed in Germany. Manufactured under ISO9000 certified management system

* German Patent No.: 100 15 833

SPECIFICATIONS

AUDIO INPUTS

Active instrument input	1/4" mono jack, unbalanced
Input impedance	approx. 220 k Ω unbalanced
Passive instrument input	1/4" mono jack, unbalanced
Input impedance	approx. 750 k Ω unbalanced
Return	1/4" mono jack, unbalanced
Input impedance	approx. 10 k Ω unbalanced

AUDIO OUTPUTS

Send/Tuner	1/4" mono jack, unbalanced
Output impedance	min. 2.2 k Ω unbalanced
Line Out	1/4" mono jack, unbalanced
Output impedance	approx. 100 Ω unbalanced
Output level	max. +4 dBu
D.I. output	XLR connector, servo-balanced
Output impedance	approx. 100 Ω balanced
Output level	max. -10 dBu
Loudspeaker connectors	1/4" mono jack, unbalanced NEUTRIK NL4MP SPEAKON® connector
Load impedance	min. 4 Ω

SYSTEM SPECIFICATIONS

Power amp output	300 Watts RMS into 4 Ω
------------------	-------------------------------

POWER SUPPLY

Mains voltages	
U.S./Canada	120 V~, 60 Hz
Europe/U.K./Australia	230 V~, 50 Hz
Japan	100 V~, 50 - 60 Hz
General export model	120/230 V~, 50 - 60 Hz
Power consumption	max. 490 W
Fuse	100 - 120 V~: T 12.6 A H 200 - 240 V~: T 6.3 A H
Mains connection	Standard IEC receptacle

PHYSICAL/WEIGHT

Dimensions (H x W x D)	approx. 5 3/4" (144,6 mm) x 19 1/8" (486 mm) x 12" (305 mm)
Weight	approx. 14 kg (30 7/8 lbs)

BEHRINGER constantly strives to maintain the highest quality standards. Modifications may be made, if necessary, without prior notice. The specifications and appearance of the equipment may therefore differ from those listed or illustrated.

ULTRABASS BX3000T

The information contained in this manual is subject to change without notice. No part of this manual may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording of any kind, for any purpose, without the express written permission of BEHRINGER Spezielle Studiotechnik GmbH.

BEHRINGER is a registered trademark.

SPEAKON® is a registered trademark of NEUTRIK with no connection whatsoever to BEHRINGER.

ALL RIGHTS RESERVED. © 2003 BEHRINGER Spezielle Studiotechnik GmbH.

BEHRINGER Spezielle Studiotechnik GmbH, Hanns-Martin-Schleyer-Str. 36-38, 47877 Willich-Münchheide II, Germany

Tel. +49 2154 9206 0, Fax +49 2154 9206 4903
