



Technical Specifications



DIGITAL MONITOR SPEAKERS MS20

24-Bit/192 kHz Digital 20-Watt Stereo Near Field Monitors

DIGITAL MONITOR SPEAKERS MS20

24-Bit/192 kHz Digital 20-Watt Stereo Near Field Monitors

- 2-way active studio monitors ideally suited for computer studios, audio and multimedia workstations and keyboard monitoring
- Built-in 2 x 10-Watt powerful amplifiers with immense headroom
- Powerful woofers and high-resolution tweeters provide an ultra-linear frequency response
- Ultra-high resolution 24-bit/192 kHz D/A converters for an incredible dynamic range
- Optical and coaxial inputs to directly connect digital audio sources by S/PDIF interface
- Two stereo analog inputs featuring 1/8" TRS and stereo RCA connectors can be used simultaneously or mixed with a digital stereo source
- Individual volume controls for both Line inputs plus Bass and Treble EQ controls
- 1/4" TRS headphone connector with auto-mute loudspeaker function easily accessible on the front panel
- Magnetically shielded for placement near computer monitors
- High-quality components and exceptionally rugged construction ensure long life
- Conceived and designed by BEHRINGER Germany

Specifications

Loudspeakers

| | |
|---------|-----------------------|
| Tweeter | Ø 65 mm (2 1/2"), 8 Ω |
| Woofers | Ø 92 mm (3 5/8"), 4 Ω |

Audio Inputs

| | |
|--------|----------------------------------|
| Line 1 | 1/8" TRS stereo, impedance 20 kΩ |
| Line 2 | 2 RCA, impedance 20 kΩ |

Digital Inputs

| | |
|-------------|-----------|
| Optical | TOSLINK |
| Coaxial | RCA |
| Converter | 24-bit |
| Sample rate | < 192 kHz |

System Specifications

| | |
|--------------------|-----------------|
| Output power | 2 x 10 W |
| Frequency response | 65 Hz to 25 kHz |

Power Supply

Mains Voltages

| | |
|-----------------------|------------------------|
| USA/Canada | 120 V~, 60 Hz |
| Europe/U.K./Australia | 230 V~, 50 Hz |
| China | 220 V~, 50 Hz |
| Japan | 100 V~, 50 - 60 Hz |
| General export model | 120/230 V~, 50 - 60 Hz |
| Power Consumption | 80 W |

Physical

| | |
|------------------------|--|
| Dimensions (H x W x D) | 9 2/5 x 6 x 7 3/8" 239 x 154 x 187 mm |
| Weight | 12.83 lbs/5.83 kg |

BEHRINGER is constantly striving to maintain the highest professional standards. As a result of these efforts, modifications may be made from time to time to existing products without prior notice. Specifications and appearance may differ from those listed or illustrated.

TECHNICAL SPECIFICATIONS AND APPEARANCES ARE SUBJECT TO CHANGE WITHOUT NOTICE AND ACCURACY IS NOT GUARANTEED. BEHRINGER IS PART OF THE MUSIC GROUP (MUSIC-GROUP.COM). ALL TRADEMARKS ARE THE PROPERTY OF THEIR RESPECTIVE OWNERS. MUSIC GROUP ACCEPTS NO LIABILITY FOR ANY LOSS WHICH MAY BE SUFFERED BY ANY PERSON WHO RELIES EITHER WHOLLY OR IN PART UPON ANY DESCRIPTION, PHOTOGRAPH OR STATEMENT CONTAINED HEREIN. COLORS AND SPECIFICATIONS MAY VARY FROM ACTUAL PRODUCT. MUSIC GROUP PRODUCTS ARE SOLD THROUGH AUTHORIZED FULLFILLERS AND RESELLERS ONLY. FULLFILLERS AND RESELLERS ARE NOT AGENTS OF MUSIC GROUP AND HAVE ABSOLUTELY NO AUTHORITY TO BIND MUSIC GROUP BY ANY EXPRESS OR IMPLIED UNDERTAKING OR REPRESENTATION. THIS MANUAL IS COPYRIGHTED. NO PART OF THIS MANUAL MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING AND RECORDING OF ANY KIND, FOR ANY PURPOSE, WITHOUT THE EXPRESS WRITTEN PERMISSION OF MUSIC GROUP IP LTD. ALL RIGHTS RESERVED. © 2012 MUSIC GROUP IP LTD. TRIDENT CHAMBERS, WICKHAMS CAY, P.O. BOX 146, ROAD TOWN, TORTOLA, BRITISH VIRGIN ISLANDS