



Technical Specifications



MULTIGATE PRO XR4400

Reference-Class 4-Channel Expander/Gate

EN **MULTIGATE PRO XR4400**

Reference-Class 4-Channel Expander/Gate

- 4 high-quality expander/gate channels
- IRC (Interactive Ratio Control) expander/gate circuitry for virtually inaudible noise suppression
- Extremely short attack time (<10 µsec) to capture ultra-high speed signals such as drums
- Parametric side chain filter with monitor function
- Independent Hold and Release controls for flexible envelope shaping
- Maximum attenuation 80 dB
- FlexLink system for ultimate master/slave configurations
- Dedicated "Traffic light" Threshold and Gain Reduction LED indicators
- Servo-balanced inputs and outputs with ¼" TRS and gold-plated XLR connectors
- High-quality components and exceptionally rugged construction ensure long life
- Conceived and designed by BEHRINGER Germany

Specifications**Audio Input**

Connectors	XLR and ¼" jack
Type	RF filtered, servo-balanced input
Impedance	50 kOhm balanced, 25 kOhm unbalanced
Max. Input Level	+21 dBu balanced and unbalanced
CMRR	typ. 40 dB, >55 dB @ 1 kHz

Audio Output

Connectors	XLR and ¼" jack
Type	Electronically servo-balanced output stage
Impedance	60 Ohms balanced, 30 Ohm unbalanced
Max. Output Level	+21 dBu, +20 dBm balanced and unbalanced

System Specifications

Frequency Response	18 Hz to 30 kHz, +/- 3 dB
Noise	>95 dBu, unweighted, 22 Hz to 22 kHz
THD	0.008% typ. @ +4 dBu, 1 kHz, Gain 1
IMD	0.01% typ. SMPTE
Crosstalk	<-100 dB, 22 Hz to 22 kHz

Gate Section

Type	UTR (Ultra Transient Response) gate
Threshold	variable (BYPASS to +10 dBu)
Attack	program dependent
Hold	variable (0 to 4 sec)
Release	variable (50 ms to 4 sec)
Range	variable (0 to -80 dB)

Expander Section

Type	IRC (Interactive Ratio Control) expander
Attack	program dependent
Ratio	variable (1:1 to 1:4)

Side-Chain Filter

Frequency	variable (100 Hz to 10 kHz)
BW (Bandwidth)	variable (2.3 to 0.7 oct.)

Function Switches

Monitor	monitors the side-chain key signal
Filter	activates the side-chain filter
Mode	gate/expander switch
Couple	activates the FlexLink function

Indicators

"+" indicator	signal is below threshold
"Hold" indicator	signal reaches the threshold
"-" indicator	signal is above threshold
Gain Reduction	8-segment LED display: 1/3/6/10/15/20/30/40 dB
LED indicator for each function switch	

Power Supply**Mains Voltages**

USA/Canada	120 V~, 60 Hz
U.K./Australia	240 V~, 50 Hz
Europe	230 V~, 50 Hz
General Export Model	100 - 120 V~, 200 - 240 V~, 50 - 60 Hz
Power Consumption	max. 20 Watts
Fuse	100 - 120 V~: T 630 mA H 200 - 240 V~: T 315 mA H
Mains Connection	Standard IEC receptacle

Physical

Dimension	1 ¾ x 19 x 8 ½" 44.5 x 483 x 217 mm
Net Weight	approx. 2.2 kg
Shipping Weight	approx. 3.5 kg

BEHRINGER is constantly striving to maintain the highest professional standards. As a result of these efforts, modifications may be made from time to time to existing products without prior notice. Specifications and appearance may differ from those listed or illustrated.

TECHNICAL SPECIFICATIONS AND APPEARANCES ARE SUBJECT TO CHANGE WITHOUT NOTICE AND ACCURACY IS NOT GUARANTEED. BEHRINGER IS PART OF THE MUSIC GROUP (MUSIC-GROUP.COM). ALL TRADEMARKS ARE THE PROPERTY OF THEIR RESPECTIVE OWNERS. MUSIC GROUP ACCEPTS NO LIABILITY FOR ANY LOSS WHICH MAY BE SUFFERED BY ANY PERSON WHO RELIES EITHER WHOLLY OR IN PART UPON ANY DESCRIPTION, PHOTOGRAPH OR STATEMENT CONTAINED HEREIN. COLORS AND SPECIFICATIONS MAY VARY FROM ACTUAL PRODUCT. MUSIC GROUP PRODUCTS ARE SOLD THROUGH AUTHORIZED FULLFILLERS AND RESELLERS ONLY. FULLFILLERS AND RESELLERS ARE NOT AGENTS OF MUSIC GROUP AND HAVE ABSOLUTELY NO AUTHORITY TO BIND MUSIC GROUP BY ANY EXPRESS OR IMPLIED UNDERTAKING OR REPRESENTATION. THIS MANUAL IS COPYRIGHTED. NO PART OF THIS MANUAL MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING AND RECORDING OF ANY KIND, FOR ANY PURPOSE, WITHOUT THE EXPRESS WRITTEN PERMISSION OF MUSIC GROUP IP LTD. ALL RIGHTS RESERVED. © 2012 MUSIC GROUP IP LTD. TRIDENT CHAMBERS, WICKHAMS CAY, P.O. BOX 146, ROAD TOWN, TORTOLA, BRITISH VIRGIN ISLANDS